

ER651625-4P

ER651625-2P

Dimension in mm

### Electrical characteristics

■ <b>Nominal Capacity</b> .....	750mAh
Stored for one year or less at 1mA, 25°C, 2.0V cut-off	
■ <b>Rated Voltage</b> .....	3.6V
■ <b>Max. Recommended Continuous Current</b> .....	10mA
Current value is determined to be the level at which the nominal capacity is obtained with an end voltage of 2V at 25°C	
■ <b>Max. Pulse Current</b> .....	30mA
Current value is obtaining 2V cell voltage when pulse is applied for 15 seconds at 50% discharge depth at 25°C	
■ <b>Storage (Recommended Max. Temperature)</b> .....	30°C
■ <b>Operating Temperature Range</b> .....	-55°C~ +85°C
■ <b>Approximate Weight</b> .....	8g

## ER651625 Specification

Primary Lithium Thionyl Chloride  
3.6V, 750mAh

### Key Features





- High and stable operating voltage
- Low self-discharge rate - less than 1% after 1 year of storage at +25°C
- Stainless steel container
- Hermetic glass-to-metal sealing
- Compliant with IEC 86-4 safety standard and EN 50020 intrinsic safety
- Non-restricted for transport



UL Component Recognition  
File Number MH45330

### Main Applications

- Alarm and security devices
- Smoke detectors
- Memory back-up
- Alarm equipment
- Industrial electronics
- Medical equipment etc.



**WARNING:** Risk of fire and burn. Do not recharge, disassemble, heat above 100°C or incinerate. Do not mix fresh batteries with used batteries.