




Equivalent Size: 1/2AA
 With 2510-2P connector



Dimension in mm

Electrical characteristics

■ Nominal Capacity	1200mAh
Stored for one year or less at 1mA, 25°C, 2.0V cut-off	
■ Rated Voltage	3.6V
■ Max. Recommended Continuous Current	30mA
Current value is determined to be the level at which the nominal capacity is obtained with an end voltage of 2.0V at 25°C	
■ Max. Pulse Current	80mA
Current value is obtaining 2.0V cell voltage when pulse is applied for 15 seconds at 50% discharge depth at 25°C	
■ Storage (Recommended Max. Temperature)	30°C
■ Operating Temperature Range	-55°C~ +85°C
■ Approximate Weight	12g

ER14250C Specification

Primary Lithium Thionyl Chloride
 3.6V, 1200mAh





Key Features

- High and stable operating voltage
- Low self-discharge rate - around 1% after 1 year of storage at +20°C
- Stainless steel container
- Hermetic glass-to-metal sealing
- Compliant with IEC 60086-4 safety standard
- Non-flammable electrolyte

UL Component Recognition
 File Number MH45330

Main Applications

- Alarm and security devices
- Smoke detectors
- Memory back-up
- Alarm equipment
- Industrial electronics
- Medical equipment etc.



WARNING: Risk of fire and burn. Do not recharge, over-discharge, disassemble, heat above 100°C or incinerate.
 **Note: The data in this document are for descriptive purposes only and subject to change without prior notice.