

Dimensions in mm

#### Available Terminations

Several types of standard terminations are available.

For details please click below [Pin Configuration Table](#)

#### Electrical characteristics

■ <b>Nominal Capacity</b> .....	2100mAh
Stored for one year or less at 3mA, 25°C, 2.0V cut-off	
■ <b>Rated Voltage</b> .....	3.6V
■ <b>Cut-off Voltage</b> .....	2.0V
■ <b>Max. Recommended Continuous Current</b> .....	400mA
Current value is determined to be the level at which the nominal capacity is obtained with an end voltage of 2.0V at 25°C	
■ <b>Max. Pulse Current</b> .....	1000mA
Typically up to 1000mA. (1000mA/0.1 second pulses, drained every 2 min at +25°C from undischarged cells with 20µA base current, yield voltage readings above 2.7V. The readings may vary according to the pulse characteristics, the temperature, and the cell's previous history. Fitting the cell with a capacitor may be recommended in severe conditions.	
■ <b>Storage (Recommended Max. Temperature)</b> .....	30°C
■ <b>Operating Temperature Range</b> .....	-55°C~ +85°C
■ <b>Approximate Weight</b> .....	20g

## ER14505M Specification

Primary Lithium Thionyl Chloride  
3.6V, 2100mAh

#### Key Features


- High and stable operating voltage
- Low self-discharge rate - around 1% after 1 year of storage at +20°C
- Stainless steel container
- Hermetic glass-to-metal sealing
- Compliant with IEC 60086-4 safety standard
- Non-flammable electrolyte

 UL Component Recognition  
File Number MH45330


#### Main Applications

- Alarm and security devices
- Smoke detectors
- Memory back-up
- Alarm equipment
- Industrial electronics
- Medical equipment etc.


Typical Discharge Profile At 25°C




Storage Characteristics



Capacity vs Current



Voltage vs Current vs Temperature



**WARNING:** Risk of fire and burn. Do not recharge, over-discharge, disassemble, heat above 100°C or incinerate.

\*\*Note: The data in this document are for descriptive purposes only and subject to change without prior notice.